

IN THE SPECIFICATION:

Please amend the specification as follows:

On page 1, after the Title and before the heading "Background of the Invention:", please insert the following new paragraph:

This application is a divisional application of applicant's parent application which is now issued as U.S. Patent 6,626,197.

Paragraph beginning on page 5, at line 2, has been amended as follows:

The lower roller holder 7 includes: a holding block 71 having a pair of lower lugs 74 oppositely formed on the holding block 71 to be respectively engaged with two lug holes 234 respectively formed on a pair of side plates 233 juxtapositionally formed on the lower runner 23; a second roller cavity 72 recessed in the holding block 71 for pivotally securing the second guiding roller R2 in the second roller cavity 72; a fourth roller cavity 77 recessed in the holding block 71 for pivotally securing the fourth guiding roller R4 in the fourth roller cavity 77; a pivot 73 secured in the holding block 71 for pivotally mounting the second and fourth guiding rollers R2, R4 on the pivot 73, with the holding block 71 snugly rested on a base 235 formed in the lower runner 23 between the two side plates 233; an extending arm 75 protruding downwardly from the holding block 71 to be engaged with a recess 231a formed in the lower runner 23 under the base 235 having a groove 76 arcuately recessed in the extending arm 75 to be engaged with a fastening wire 232 provided for fastening a ferrule 231 of the lower runner 23, thereby fastening the extending arm 75 and the lower roller holder 7 stably on the lower runner 23 for well protecting the guiding rollers R2, R4 in the lower holder 7.